

Hi-Power Dexron III series

Product Description:

Hi-Power ATF DEXRON III consists of high quality paraffinic base oil and additive systems to provide excellent foam resistance, corrosion and wear protection. It is reinforced with specially selected friction modifiers to meet the demanding frictional requirements of the automatic transmission. Shelf life provided is 3 to 3½ years.

Applications / Benefits:

1. Ensures long servicing life.
2. Provides high form stability.
3. Superb anti-wear properties.
4. Smoother & quieter automatic transmission
5. Excellent frictional, oxidative and thermal stability.
6. Provides anti rust protection and lower sludge formation.
7. Provides good start operation in cold climates by low temperature fluidity.

Typical Characteristics:

Characteristics Method	Unit	Method	Typical Value
Kinematic Viscosity @ 100 °C	cSt	ASTM D445	7.3
Kinematic Viscosity @ 40 °C	cSt	ASTM D445	35.7
Viscosity Index			175
Appearance	-	-	Red
Flash Point (PMCC)	°C	ASTM D93	195
Pour Point	°C	-	-25

Specifications, Approvals & Recommendations:

GM Dexron III, Dexron III E
Mercon fLUIDS
Allison C-4 Fluid
Caterpillar TO-2 Lubricant
MIL-L-2104 D