

Hi-Power 4T SG series

Product Description:

Hi-Power 4T SG grade which consists of high-grade wear resistance additives, viscosity improver, corrosion inhibitor & Anti-oxidant. It is specially formulated for use in motorcycle gasoline (petrol) engines i.e. 4-stroke. This engine oil is manufactured with high safety measure and quality control according to ISO 9001:2008 standard. Recommended shelf life is 3 to 3½ years, but normally can last for 5 years.

Recommended for almost all the motorcycles:
Yamaha, Suzuki, Kawasaki, Honda, Kriss, Jaguh, BMW,

Applications / Benefits:

1. Ensures maximum engine performance and power.
2. Reduces oxidation during engine operation.
3. Reduces carbon, acid, wax, deposits and sludge formations.
4. Ensures smoother, cooler and quieter engine performances.
5. Protection against engine internal corrosion & rust.
6. Keeps engine running cleaner & more efficient.
7. Good for smaller bikes or older bikes.

Typical Characteristics:

Test Description	Method	15W-50	20W-50
SAE Viscosity Grade	SAE J 300	15W-50	20W-50
Specific Gravity @ 15 °C	ASTM D 4052	0.885	0.893
Flash Point, °C	ASTM D 92	224	235
Pour Point, °C	ASTM D 97	-24	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	145	175
cSt @ 100°C	ASTM D 445	18.9	19.5
Viscosity Index	ASTM D 2270	148	128
TBN, mgKOH/g	ASTM D 2896	6.3	6.3
Color	ASTM D 1500	<3.5	<3.5

Specifications, Approvals & Recommendations:

-JASO MA2
-API SG