

Power Up PAO Fully Synthetic SN series

Product Description:

Power Up Fully Synthetic SN LS Series engine oil is blended with highest quality additive and basestock. It is a premium quality "Mid SAPS" passenger car lubricants that specifically formulated with ultimate active clean technology. It is blended with high quality Polyalphaolefins (PAO) base fluid and the high technology core additive package that meets the requirements of ACEA C3 and MB-Approval 229.51. It is suitable for use in the widest range of modern Passenger Cars and small vehicles include Gasoline vehicles as well.

Applications / Benefits:

1. Ensures maximum engine performance and power.
2. Highly recommended for both smaller engines and high performance bigger engines capacity
3. Recommended Min. 12,000km per oil change, but not more than 17,000km. (This is subjected to engine in good condition, for worn out engine shorter mileage per oil change).
4. Reduces carbon, acid and sludge formations.
5. Ensures smoother, cooler and quieter engines.
6. Increase the power of the engine.
7. Keeps engine running clean and efficient.
8. Ensure Cleaner engine after usage.

Typical Characteristics:

Test Description	Method	5W20	5W30	10W30	5W40	5W50
SAE Viscosity Grade	SAE J 300					
Specific Gravity @ 15 °C	ASTM D 4052	0.847	0.850	0.852	0.855	0.857
Flash Point, °C	ASTM D 92	212	214	218	216	218
Pour Point , °C	ASTM D 97	-39	-39	-36	-39	-39
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	47.7	70.1	69.8	91.9	119
cSt @ 100°C	ASTM D 445	8.5	11.8	11.3	14.5	18.1
Viscosity Index	ASTM D 2270	156	165	155	164	170
TBN, mgKOH/g	ASTM D 2896	7.8	7.8	7.8	7.8	7.8
Color	ASTM D 1500	<2.5	<2.5	<2.5	<2.5	<2.5
CCS, cP	ASTM D 5293	5318	5215	5322	5536	5850

Specifications, Approvals & Recommendations:

- API SN
- ACEA A1/B1-12
- ACEA A5/B5-12
- ACEA C2-12
- ACEA C3-12
- ACEA A3/B3-08
- ACEA A3/B4-08